

Leica Lino L2+

Simply perfect all along the line!



The time-consuming and tedious drawing of lines on the wall is a thing of the past. The Leica Lino L2+ projects them exactly, quickly and easily – allowing you to concentrate on the job in hand. The improved emergence angle ensures outstanding visibility and extension of the laser lines and allow perfect leveling and alignment at long distances.

- Emergence angle of 180°
- Pulse function with power-saving mode
- Modern, ergonomic housing
- Exact 90° angle
- Very easy to use




- Target plate
- Magnetic multifunction adapter
- Alkaline batteries (type AA, 4 × 1.5V)
- Pouch

Technical specifications:	
Range	up to 15 m depending on lighting conditions
Range with detector	> 30 m
Levelling accuracy @ 5 m	± 1.0 mm
Self-levelling range	4° ± 0.5°
Accuracy of horizontal line @ 5 m	± 1.5 mm
Vertical accuracy @ 3 m line length	± 0.75 mm
Beam divergence	< 180°
Laser type	635 nm, laser class II
Batteries	type AA 4 × 1.5 V
Protection class splash water/ dust proof	IP54
Operating temperature	-10 °C to 40 °C
Storage temperature	-25 °C to 70 °C
Dimensions (H × D × W)	117.8 × 130.7 × 75.4 mm
Weight without batteries	370 g
Tripod thread	1/4"



Self-levelling

The instrument is set up quickly and effortlessly to project horizontal or vertical lines. Minor angular mis-alignments of $\pm 4^\circ$ are compensated automatically. If the tilt is outside these limits, the device does not project any lines and errors are therefore prevented.



Extra long laser lines

The improved emergence angle ensures outstanding visibility and extension of the laser line for perfect levelling and alignment at long distances. It is possible, e.g., to transfer reference points from one wall to the next. Leave your spirit level and string in your tool box.



Working in bright conditions

The pulse function is not just an energy-saving mode: it also allows you to locate the laser lines using a laser detector, even in very bright lighting conditions. A series of acoustic signals from the detector indicates the precise position of the laser beam plane.



Lock function

You can manually switch off the self-levelling features using the lock function. The laser line can then be projected at any angle. The lock function also serves as transport protection.