



Prexiso XL2

Cross Line Laser

The Prexiso XL2 Cross Line Laser can be used wherever accurate verticals and horizontals are required for alignment. Water-level and line drawing on walls become redundant.

Self-levelling

It is not necessary to align the device tediously to obtain horizontal or vertical lines. The Prexiso XL2 compensates over a range of $\pm 5^\circ$ automatically.

Perfect along the line

Whether horizontal, vertical or crossed – the red lines are a reliable reference to align everything in your room.

Easy to use

The Prexiso XL2 is intuitive to operate due to one button only.

Lock-function

Lock for projecting at any angle and transport protection.

Easier, faster and better:

- Laying tiles, carpets or other flooring
- Wallpaper hanging
- Installing kitchens
- Building-up dry walls
- Installing ceilings
- Levelling or aligning any other structural elements or objects



Functionalities	1 horizontal line plus + 1 vertical line
Accuracy	$\pm 2 \text{ mm}/5 \text{ m}$
Working range	10 m
Sensitivity range	self-levelling $\pm 5^\circ$
Fan angles of horizontal and vertical directions	greater than 130°
Battery	3 AA size batteries
Working hours	more than 16 hours (both lines on)
Working temperature range	14°F to 104°F (-10°C to $+40^\circ\text{C}$)
Storage temperature range	-4°F to 158°F (-20°C to $+70^\circ\text{C}$)
Laser classification	Class 2 laser
Dimensions	$109 \times 63 \times 87 \text{ mm}$
Weight	298 g (excluding batteries)