



## Leica FlexLine TS02 Total Station – Ideal today, perfect tomorrow



Angle Measurement (Hz, V)		
Accuracy (Standard deviation ISO-17123-3)	3" (1 mgon), 5" (1.5 mgon), 7" (2 mgon)	optional
Method	Absolute, continuous, diametrical	
Display resolution	0.1" / 0.1 mgon / 0.01 mil	
Compensation	Quadruple axis compensation (Setting On, Off)	
Compensator Setting accuracy	1", 1.5", 2"	



Distance Measurement with Reflector		
Range Round prism GPR1	3'500 m	
Range Reflective tape (60 mm x 60 mm)	250 m	
Accuracy / Measurement time (Standard deviation ISO-17123-4)	Standard: 1.5 mm+2 ppm / typ. 2.4 s, Fast: 3 mm+2 ppm / typ. 0.8 s, Tracking: 3 mm+2 ppm / typ. <0.15 s	



Distance Measurement without Reflector		
Range (90% reflective)		
FlexPoint	30 m	optional
PinPoint – Power	> 400 m <sup>3</sup>	optional
PinPoint – Ultra	> 1000 m <sup>3</sup>	optional
Accuracy / Measurement time (Standard deviation ISO-17123-4)	2 mm+2 ppm <sup>2</sup> / typ. 3 s	
Laser dot size	At 30 m: approx. 7 mm x 10 mm, At 50 m: approx. 8 mm x 20 mm	



Data storage / Communication		
Extended internal memory	Max.: 24'000 fixpoints, Max.: 13'500 measurements	
USB memory stick	1 Gigabyte, Transfer time 1'000 points/second	optional
Interfaces	Serial (Baudrate 1'200 to 115'200) USB Type A and mini B, Bluetooth® Wireless	optional
Data formats	GSI / DXF / LandXML / CSV / user definable ASCII formats	



Electronic Guide Light for Stake Out (optional)		
Working Range (average atmospheric conditions)	5 m – 150 m	optional
Positioning accuracy	5 cm at 100 m	optional



General		
Telescope		
Magnification	30 x	
Resolving power	3"	
Field of view	1° 30' (1.66 gon) / 2.7 m at 100 m	
Focusing range	1.7 m to infinity	
Reticle	Illuminated, 5 brightness levels	
Keyboard and Display		
Display	Graphics, 160 x 280 pixels, illuminated, 5 brightness levels	
Keyboard	Standard keyboard Alpha-numerical keyboard, Second keyboard	optional
Operating System		
Windows CE	5.0 Core	
Laserplummet		
Type	Laser point, 5 brightness levels	
Centering accuracy	1.5 mm at 1.5 m Instrument height	
Battery		
Type	Lithium-Ion	
Operating time	approx. 20 hours <sup>1</sup>	
Weight		
Total Station including GEB211 and tribrach	5.1 kg	
Environmental		
Temperature range (operation)	-20° C to +50° C (-4° F to +122° F) Arctic Version -35° C to 50° C (-31° F to +122° F)	optional
Dust & splash proof (IEC 60529)	IP55	
Humidity	95%, non condensing	



FlexField Onboard Software		
Application programs	Topography (Orientation & Surveying), Stake Out, Resection, Height Transfer, Construction, Area (Plan & Surface), DTM Volume calculation, Tie Distance (MLM), Remote Height, Hidden Point, Backsight Check, Offset, Reference Line	
Application programs	Reference Arc, Reference Plane, COGO, Road 2D	optional